

General Equipment Specifications: General Duty
Controls: (1) AC variable speed drive mounted to side of conveyor. Controller will have remote start/stop feature
Electrics: 110/220 VAC, Single Phase, 60Hz, Nema 12
Construction: Heavy-duty painted steel, with adjustable (+/- 2") foot pads.
Side Guides: Fixed
Belt Type: Modular plastic with 1.5" tall cleats on 8" centers - Habasit M2510
Belt Width: 18" - 17" useable
Motor/Reducer: World Wide Electric AC motor with attached World Wide Electric painted gear reducers
Pneumatics: None
Infeed hopper: Painted steel frame with stainless steel hopper and slide gate, approx. 5 cubic feet capacity
Casters: None

This document is confidential and is the property of Tridyne Process Systems ("Tridyne"). It may not be copied or reproduced in any manner without the expressed written consent of Tridyne. This document is an unpublished work. Tridyne maintains the work as confidential information. Those having access to this work may not copy, use or disclose the information in this work unless expressly authorized by Tridyne

TRIDYNE PROCESS SYSTEMS
80 ALLEN ROAD
SOUTH BURLINGTON, VT 05403
TEL 802 863-6873 FAX 802 860-1591

TITLE: WEST STAR INCLINE CONVEYOR
DRAWING NO: WESTSYSL DATE: 05-24-2016
DRAWN BY: ID REV I

ALL DIMENSIONS ARE PRELIMINARY AND SUBJECT TO CHANGE. INTENTION IS TO OUTLINE PRIMARY CHARACTERISTICS OF PROPOSED SCALE SYSTEM. DO NOT BUILD FROM THIS DWG. ALL DIMENSIONS ARE IN INCHES UNLESS NOTED.