


D.O.T. COMPLIANT

FUEL HAULER TRAILERS

Standard Features

FRAME	HEAVY DUTY STRUCTURAL CHANNEL FRAME AND FLAT TANK SUPPORT PLATFORM
TANK	BOLT-ON, SPRING CUSHIONED HIP TANK W/ROLL GUARDS, STAINLESS STEEL FUEL GAUGE, 3/16" TANK STEEL THICKNESS, (2) 2" TANK FILL LOCATIONS W/ LOCKABLE PRE-VENT CAPS WITH TANK VENTING STAINLESS STEEL BOTTOM TANK DRAIN PORT, LOCKING 2" FUEL SHUTOFF VALVE ON LOWER LEFT FRONT CORNER OF TANK
SUSPENSION	HIGHWAY RATED AXLES, TIRES AND WHITE SPOKE WHEELS; UNDER-SLUNG SLIPPER SPRINGS
BRAKES	4-WHEEL ELECTRIC BRAKES W/BREAKAWAY KIT
JACK	7,000 LB. DROP LEG, BOLT ON, TOP-WIND TONGUE JACK
PLATFORM	12" REAR PLATFORM, STEP AND GRAB HANDLE
FENDERS	HEAVY DUTY FLAT TOP STEEL FENDERS WITH FRONT RUBBERIZED COATING, AND BLACK SPLASH GUARDS
HITCH	2-5/16" ADJUSTABLE BALL COUPLER WITH (2) 3/8" SAFETY CHAINS AND ID TAGS
LIGHTS	D.O.T. LED LIGHTS CONFORMING TO CFR49 AND ENCLOSED IN CONDUIT OR LOOM WITH 7-WAY RV CONNECTOR
COLOR	TRAILER: BLACK TANK: WHITE
OTHER	CONSPICUITY TAPE, SAFETY SIGNS, DUO LIFT DECAL, (4) FUEL PLACARDS (NOT INSTALLED), 17 DIGIT VIN, ID PLATE AND MANUFACTURERS STATEMENT OF ORIGIN, MANUAL CANISTER, ANNUAL FEDERAL INSPECTION AND CERTIFICATE

Technical Data

MODEL	GVWR	AXLES	FRAME	TANK	WHEELS	EMPTY WT.
FH500D	7,000 LBS	(2) 3,500 Lb. Capacity Tandem Axles, 15'8" L X 84" W X 6' H	6" Heavy Duty Structural Channel Frame	500 Gallon Hip Tank with (1) Baffle, 3/16" Steel, D.O.T.. Approved	225/75R15D on 15" x 6" - 6 on 5.5" White Spoke Wheels	3,000 LBS
FH500D	14,000 LBS	(2) 7,000 Capacity Tandem Axles, 15'8" L X 84" W X 6' H	6" Heavy Duty Structural Channel Frame	500 Gallon Hip Tank with (1) Baffle, 3/16" Steel, D.O.T.. Approved	225/75R15D on 15" x 6" - 6 on 5.5" White Spoke Wheels	3,400 LBS
FH750D	14,000 LBS	(2) 7,000 Capacity Tandem Axles, 17'4" L X 84" W X 6' H	7" Heavy Duty Structural Channel Frame	750 Gallon Hip Tank with (2) Baffles, 3/16" Steel, D.O.T. Approved	235/80R16E on 16" x 8" - 8 on 6.5" White Spoke Wheels	3,900 LBS
FH990D UNAVAILABLE IN CANADA	14,000 LBS	(2) 7,000 Capacity Tandem Axles, 19'6" L X 84" W X 6' H	7" Heavy Duty Structural Channel Frame	990 Gallon Hip Tank with (3) Baffles, 3/16" Steel, D.O.T.. Approved	235/80R16E on 16" x 6" - 8 on 6.5" White Spoke Wheels	4,500 lbs
FH1000D	14,500 LBS	(2) 7,000 Capacity Tandem Axles, 20' L X 84" W X 6' H	76" Heavy Duty Structural Channel Frame	(2) 500 Gallon Hip Tank with (1) Baffle, 3/16" Steel, D.O.T.. Approved NOTE: DIESEL FUEL IN BOTH TANKS CAN BE COMBINED OR SEPARATELY DISPENSED.	235/80R16E on 16" x 8" - 8 on 6.5" White Spoke Wheels	5,000 LBS


PHONE: (800) 243-2583 EMAIL: SALES@DUOLIFT.COM
WEB: WWW.DUOLIFT.COM
Effective JULY 2024